

# WebTech 5000 Locator



The WebTech 5000 Locator is a feature-rich wireless GPS locator device at the heart of the WebTech Quadrant Vehicle Services System™. Fleet managers can access the mapping and reporting capabilities of the Locators through the web-based Quadrant system.

#### Benefits - Experience the WebTech Difference

- Increase mobile workforce productivity
- Lower operating costs
- Improve the safety and security of mobile assets

#### Features - Get the WebTech Edge

##### Location Services

- GPS Tracking
- Geofencing
- Mapping
- Reporting
- In-vehicle Navigation

##### Communication Services

- Two-way Messaging
- Digital Forms
- MDT2000E (optional)

##### Internet Services

- Email
- Internet Access
- Enterprise Connectivity
- Maintenance Scheduling

##### Telemetry Services

- Door Lock/Unlock
- Engine Immobilization
- Temperature Monitoring

##### Additional supported options

- Internal Battery - supports asset and trailer tracking applications, auto-recharging capability
- Navigation - Use the GPS NMEA port to enable in-vehicle mapping and turn-by-turn instructions from a laptop or hand held.

Contact a WebTech sales representative today for a personal live demo. Call 1.866.287.0135 or email [sales@webtechwireless.com](mailto:sales@webtechwireless.com)

# WebTech 5000 Locator

<b>Certification</b>	PTCRB/FCC/IC UL/CSA/CE
<b>Networks Supported</b>	GSM/SMS/GPRS 850/1900 MHz or 900 / 1800 MHz
<b>Physical Specifications</b>	Dimensions - 105 x 95 x 30 mm (4.30" x 3.75" x 1.18") Weight - 125g (4.4 oz.)
<b>Power Specifications</b>	Power - Input Voltage - 9 - 36 VDC Current (at 12 VDC) - Transit 1000 mA (maximum bursts) - Standby (receive) - 100 mA - Sleep (ignition off) - 10 mA
<b>Environmental</b>	Operating Temperature: -20°C to +70°C Storage Temperature: -40°C to +80°C Humidity: 95% Max (non-condensing)
<b>Connectors</b>	RS-232 - DCE - DB-9 connector Power - 3 wire (ignition, battery, ground) RF - SMA (female) GPS - SMC (female)
<b>Interoperable Devices</b>	Windows CE/ Windows Mobile Laptop Computers WebTech Mobile Data Terminals
<b>Protocols</b>	PPP on serial port NMEA Transparent Pass Through
<b>Included</b>	Installation Manual Active GPS antenna GSM 1/4 Wave Stubby Antenna Power and Serial Cable Telemetry (2 inputs, 2 outputs)
<b>Hardware Options</b>	Internal Lithium Polymer Battery (1900mA hour)
<b>Optional Accessories</b>	Panic button (in-vehicle / remote) External roof mount RF & GPS antennae Driver ID MDT Locator TrackBox and more...



WebTech Wireless Inc.  
215 - 4299 Canada Way  
Burnaby, BC, Canada, V5G 1H3  
Tel: +(1) 604.434.7337  
Fax: +(1) 604.434.5270  
info@webtechwireless.com  
www.webtechwireless.com

WebTech Wireless United Kingdom

Wyvols Court  
Old Basingstoke Road,  
Swallowfield, Reading, Berkshire  
United Kingdom  
RG71WY  
Tel: +44 118 988 0233  
Fax: +44 118 988 0333